



- NOTE:
- 1.) SUCTION AND DISCHARGE PORTS DEPENDENT ON DIRECTION OF ROTATION.
 - 2.) ALL STANDARD AND OPTIONAL PORT CONNECTION PIPE PLUGS ARE 1/8" NPT.
 - 3.) (2) 1/8" NPT PIPE CONNECTION PORTS ARE STANDARD WITH DOUBLE CAN OPTION. STANDARD ASSEMBLY IS LEFT/TOP CONNECTION PORT ORIENTATION WHEN VIEWED FROM PUMP END. CUSTOMER TO SPECIFY WHEN RIGHT/TOP CONNECTION PORT ORIENTATION IS REQUIRED.

REF	ADDED OPTIONAL FLANGE REVISION UPDATE	03/27/01	DATE
-----	---------------------------------------	----------	------

SECTION/PAGE	MODEL GMH6 / 301
EFFECTIVE	03/27/01
SUPERSEDES	04/01/98

ALL DIMENSIONS ARE IN INCHES

Isochem **PULSAFEEDER**
A Unit of IDEX Corporation

DIMENSIONAL DRAWING
GMH6 PUMP UNMOUNTED
WITH PEDESTAL ASSY

DWN BY: CLA
DATE: 10/09/97

SD-2873