

Safety Data Sheet
DEVTRAN 224V PART B



Bulk Sales Reference No.:
SDS Revision Date:
SDS Revision Number:

Sales
Order: {SalesOrd}
DC224G0908
10/08/2015
A2-3

1. Identification of the preparation and company

1.1. Product identifier

Product Identity DEVTRAN 224V PART B
Bulk Sales Reference No. DC224G0908

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended Use See Technical Data Sheet.
Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name International Paint LLC
6001 Antoine Drive
Houston Texas 77091

Emergency

CHEMTREC (USA) (800) 424-9300
International Paint (713) 682-1711
Poison Control Center (800) 854-6813
Customer Service
International Paint (800) 589-1267
Fax No. (800) 631-7481

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Flam. Liq. 3;H226 Flammable liquid and vapor.
Skin Corr. 1B;H314 Causes severe skin burns and eye damage.
Eye Dam. 1;H318 Causes serious eye damage.
Repr. 2;H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
Aquatic Chronic 2;H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



Danger.

H226 Flammable liquid and vapor.
H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.
H361 Suspected of damaging fertility or the unborn child.
H411 Toxic to aquatic life with long lasting effects.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P260 Do not breathe mist / vapors / spray.

P262 Do not get in eyes, on skin, or on clothing.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P308+313 IF exposed or concerned: Get medical advice/attention.

P310 Immediately call a POISON CENTER or doctor / physician.

P331 Do NOT induce vomiting.

P363 Wash contaminated clothing before reuse.

P370 In case of fire: Use water spray, fog, or regular foam..

P391 Collect spillage.

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating Health: 3* Flammability: 2 Reactivity: 0

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Barium sulfate CAS Number: 0007727-43-7	10 - 25	----	[1][2]
FATTY ACIDS, C18-UNSATD., DIMERS, REACTION PRODUCT CAS Number: 0068410-23-1	10 - 25	Eye Dam. 1;H318	[1]
BUTYL ACETATE CAS Number: 0000540-88-5	10 - 25	Flam. Liq. 2;H225	[1][2]
Phenol, 4-nonyl-, branched CAS Number: 0084852-15-3	10 - 25	Repr. 2;H361fd Acute Tox. 4;H302 Skin Corr. 1B;H314 Aquatic Acute 1;H400 Aquatic Chronic 1;H410	[1]
Quartz CAS Number: 0014808-60-7	1.0 - 10	Acute Tox. 4;H332 STOT RE 2;H373	[1][2]
Talc CAS Number: 0014807-96-6	1.0 - 10	----	[1][2]
Wollastonite (Ca(SiO3)) CAS Number: 0013983-17-0	1.0 - 10	----	[1]
Petroleum naphtha CAS Number: 0064742-95-6	1.0 - 10	Asp. Tox. 1;H304 Aquatic Chronic 2;H411 (Self Classification)	[1]
Kaolin CAS Number: 0001332-58-7	1.0 - 10	----	[1][2]
Phenol CAS Number: 0000108-95-2	0.10 - 1.0	Muta. 2;H341 Acute Tox. 3;H331 Acute Tox. 3;H311 Acute Tox. 3;H301	[1][2]

	STOT RE 2;H373	
	Skin Corr. 1B;H314	

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing. Contains an ingredient which may cause reproductive disorders based on animal data (See Section 2 and Section 15 for each ingredient).
Inhalation	Harmful if inhaled. May cause allergic respiratory reaction. May cause mucous membrane and respiratory tract irritation, tightness of chest, headache, shortness of breath and dry cough. May cause asthma-like symptoms to occur. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.
Eyes	Causes severe eye irritation. Avoid contact with eyes.
Skin	Causes skin irritation. May be harmful if absorbed through the skin.
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.
Chronic effects	Birth defect hazard. Contains an ingredient which can cause birth defects (See Section 2 and Section 15 for each ingredient). Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.

5. Fire-fighting measures

5.1. Extinguishing media

CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient.

CAUTION: For mixtures containing alcohol or polar solvent, alcohol-resistant foam may be more effective.

SMALL FIRES: Use dry chemical, CO₂, water spray or regular foam. LARGE FIRES: Use water spray, fog, or regular foam. Do not use straight streams. Move containers from fire area if you can do so without risk.

5.2. Special hazards arising from the substance or mixture

HIGHLY FLAMMABLE MATERIALS: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water.

5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No. 128

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

7. Handling and storage

7.1. Precautions for safe handling

Handling

Vapors may cause flash fire or ignite explosively.

In Storage

Keep away from heat, sparks and flame.

7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Do not get in eyes, on skin or clothing.

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000108-95-2	Phenol	OSHA	5 ppm TWA; 19 mg/m3 TWA
		ACGIH	5 ppm TWA
		NIOSH	5 ppm TWA; 19 mg/m3 TWA15.6 ppm Ceiling (15 min); 60 mg/m3 Ceiling (15 min)250 ppm IDLH
		Supplier	
		OHSA, CAN	5 ppm TWA
		Mexico	5 ppm TWA LMPE-PPT; 19 mg/m3 TWA LMPE-PPT10 ppm STEL [LMPE-CT]; 38 mg/m3 STEL [LMPE-CT]
		Brazil	4 ppm TWA LT; 15 mg/m3 TWA LT
0000540-88-5	BUTYL ACETATE	OSHA	200 ppm TWA; 950 mg/m3 TWA
		ACGIH	200 ppm TWA
		NIOSH	200 ppm TWA; 950 mg/m3 TWA1500 ppm IDLH (10% LEL)
		Supplier	
		OHSA, CAN	200 ppm TWA
		Mexico	200 ppm TWA LMPE-PPT; 950 mg/m3 TWA LMPE-PPT250 ppm STEL [LMPE-CT]; 1190 mg/m3

DC224G0908_A2

		STEL [LMPE-CT]	
0001332-58-7	Kaolin	Brazil	
		OSHA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
		ACGIH	2 mg/m3 TWA (particulate matter containing no asbestos and
		NIOSH	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
		Supplier	
		OHSA, CAN	2 mg/m3 TWA (containing no Asbestos and
		Mexico	10 mg/m3 TWA LMPE-PPT20 mg/m3 STEL [LMPE-CT]
		Brazil	
0007727-43-7	Barium sulfate	OSHA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
		ACGIH	10 mg/m3 TWA
		NIOSH	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)
		Supplier	
		OHSA, CAN	10 mg/m3 TWA
		Mexico	
		Brazil	
		0013983-17-0	Wollastonite (Ca(SiO3))
ACGIH			
NIOSH			
Supplier			
OHSA, CAN			
Mexico			
Brazil			
0014807-96-6	Talc		
		ACGIH	2 mg/m3 TWA (particulate matter containing no asbestos and
		NIOSH	2 mg/m3 TWA (containing no Asbestos and
		Supplier	
		OHSA, CAN	2 mg/m3 TWA (containing no Asbestos and
		Mexico	2 mg/m3 TWA LMPE-PPT (respirable fraction)
		Brazil	
		0014808-60-7	Quartz
ACGIH	0.025 mg/m3 TWA (respirable fraction)		
NIOSH	0.05 mg/m3 TWA (respirable dust)50 mg/m3 IDLH (respirable dust)		
Supplier			
OHSA, CAN	0.10 mg/m3 TWA (designated substances regulation, respirable, listed under Silica, crystalline)0.10 mg/m3 TWA (respirable fraction, listed under Silica, crystalline)		
Mexico	0.1 mg/m3 TWA LMPE-PPT (respirable fraction)		
Brazil			
0064742-95-6	Petroleum naphtha		
		ACGIH	
		NIOSH	
		Supplier	
		OHSA, CAN	
		Mexico	
		Brazil	

DC224G0908_A2

0068410-23-1	FATTY ACIDS, C18-UNSATD., DIMERS, REACTION PRODUCT	OSHA	
		ACGIH	
		NIOSH	
		Supplier	
		OHSA, CAN	
		Mexico	
0084852-15-3	Phenol, 4-nonyl-, branched	OSHA	
		ACGIH	
		NIOSH	
		Supplier	
		OHSA, CAN	
		Mexico	
		Brazil	

Health Data

CAS No.	Ingredient	Source	Value
0000108-95-2	Phenol	NIOSH	Skin eye
0000540-88-5	BUTYL ACETATE	NIOSH	Eye and throat irritation CNS depression
0001332-58-7	Kaolin	NIOSH	Skin and mucous membrane injury respiratory effects
0007727-43-7	Barium sulfate	NIOSH	Eye nose
0013983-17-0	Wollastonite (Ca(SiO3))	NIOSH	
0014807-96-6	Talc	NIOSH	(containing asbestos); Fibrotic pneumoconiosis; (containing no asbestos); Nonmalignant respiratory effects
0014808-60-7	Quartz	NIOSH	Chronic lung disease (silicosis)
0064742-95-6	Petroleum naphtha	NIOSH	
0068410-23-1	FATTY ACIDS, C18-UNSATD., DIMERS, REACTION PRODUCT	NIOSH	
0084852-15-3	Phenol, 4-nonyl-, branched	NIOSH	

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000108-95-2	Phenol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0000540-88-5	BUTYL ACETATE	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0001332-58-7	Kaolin	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0007727-43-7	Barium sulfate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0013983-17-0	Wollastonite (Ca(SiO3))	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0014807-96-6	Talc	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No

DC224G0908_A2

		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0014808-60-7	Quartz	OSHA	Select Carcinogen: Yes
		NTP	Known: Yes; Suspected: No
		IARC	Group 1: Yes; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-95-6	Petroleum naphtha	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0068410-23-1	FATTY ACIDS, C18-UNSATD., DIMERS, REACTION PRODUCT	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0084852-15-3	Phenol, 4-nonyl-, branched	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Eyes	Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Depending on the site-specific conditions of use, provide adequate ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties

Appearance	Coloured Liquid
Odour threshold	Not Measured
pH	9
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	98 (°C) 208 (°F)
Flash Point	27 (°C) 80 (°F)
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 1 Upper Explosive Limit: No Established Limit
vapor pressure (Pa)	Not Measured

DC224G0908_A2

Vapor Density	Heavier than air
Specific Gravity	1.41
Solubility in Water	Not Measured
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	No Established Limit Not Measured
VOC %	Refer to the Technical Data Sheet or label where information is available.

10. Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

HIGHLY FLAMMABLE MATERIALS: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water.

11. Toxicological information

Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr
Barium sulfate - (7727-43-7)	3,000.00, Mouse - Category: 5	No data available	No data available	No data available
FATTY ACIDS, C18-UNSATD., DIMERS, REACTION PRODUCT - (68410-23-1)	No data available	No data available	No data available	No data available
BUTYL ACETATE - (540-88-5)	4,100.00, Rat - Category: 5	2,000.00, Rabbit - Category: 4	No data available	No data available
Phenol, 4-nonyl-, branched - (84852-15-3)	580.00, Rat - Category: 4	2,031.00, Rabbit - Category: 5	No data available	No data available
Quartz - (14808-60-7)	No data available	No data available	No data available	No data available
Talc - (14807-96-6)	No data available	No data available	No data available	No data available
Wollastonite (Ca(SiO3)) - (13983-17-0)	No data available	No data available	No data available	No data available
Petroleum naphtha - (64742-95-6)				

DC224G0908_A2

	6,800.00, Rat - Category: NA	3,400.00, Rabbit - Category: 5	No data available	No data available
Kaolin - (1332-58-7)	No data available	No data available	No data available	No data available
Phenol - (108-95-2)	317.00, Rat - Category: 4	630.00, Rabbit - Category: 3	No data available	No data available

Item	Category	Hazard
Acute Toxicity (mouth)	Not Classified	Not Applicable
Acute Toxicity (skin)	Not Classified	Not Applicable
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	1B	Causes severe skin burns and eye damage.
Eye damage/irritation	1	Causes serious eye damage.
Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	Not Classified	Not Applicable
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	Not Classified	Not Applicable
Reproductive Toxicity	2	Suspected of damaging fertility. Suspected of damaging the unborn child.
Specific target organ systemic toxicity (single exposure)	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	Not Classified	Not Applicable
Aspiration hazard	Not Classified	Not Applicable

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Barium sulfate - (7727-43-7)	59,000.00, Poecilia sphenops	32.00, Daphnia magna	Not Available
FATTY ACIDS, C18-UNSATD., DIMERS, REACTION PRODUCT - (68410-23-1)	Not Available	Not Available	Not Available
BUTYL ACETATE - (540-88-5)	327.00, Pimephales promelas	Not Available	1,300.00 (24 hr), Chlorococcales
Phenol, 4-nonyl-, branched - (84852-15-3)	Not Available	Not Available	Not Available
Quartz - (14808-60-7)	Not Available	Not Available	Not Available
Talc - (14807-96-6)	Not Available	Not Available	Not Available
Wollastonite (Ca(SiO ₃)) - (13983-17-0)	Not Available	Not Available	Not Available
Petroleum naphtha - (64742-95-6)	9.22, Oncorhynchus mykiss	6.14, Daphnia magna	19.00 (72 hr), Selenastrum capricornutum
Kaolin - (1332-58-7)	Not Available	Not Available	Not Available
Phenol - (108-95-2)	3.73, Oncorhynchus gorbuscha	3.29, Ceriodaphnia dubia	46.42 (96 hr), Pseudokirchneriella subcapitata

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available

13. Disposal considerations

13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

14.1. UN number UN 1263

14.2. UN proper shipping name PAINT

14.3. Transport hazard class(es)

DOT (Domestic Surface Transportation)		IMO / IMDG (Ocean Transportation)	
DOT Proper Shipping Name	PAINT	IMDG Proper Shipping Name	PAINT
DOT Hazard Class	3	IMDG Hazard Class	3
		Sub Class	3
UN / NA Number	UN 1263		
DOT Packing Group	III	IMDG Packing Group	III
CERCLA/DOT RQ	2150 gal. / 25202 lbs.	System Reference Code	2

14.4. Packing group III

14.5. Environmental hazards

IMDG Marine Pollutant: Yes (Phenol, 4-nonyl-, branched)

14.6. Special precautions for user

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification B2 D2A E

DOT Marine Pollutants (10%)

Phenol, 4-nonyl-, branched

DOT Severe Marine Pollutants (1%):

(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%) :

Benzene, ethyl- (1000 lb final RQ; 454 kg final RQ)

Benzene, 1,2-dimethyl- (1000 lb final RQ; 454 kg final RQ)

Phenol (1000 lb final RQ; 454 kg final RQ)

DC224G0908_A2

BUTYL ACETATE (5000 lb final RQ (listed under Butyl acetate); 2270 kg final RQ (listed under Butyl acetate))

Benzene, 1,4-dimethyl- (100 lb final RQ; 45.4 kg final RQ)

Xylenes (o-, m-, p- isomers) (100 lb final RQ; 45.4 kg final RQ)

EPCRA 302 Extremely Hazardous (>.1%) :

Phenol (500 lb lower TPQ; 10000 lb upper TPQ)

EPCRA 313 Toxic Chemicals (>.1%) :

1,2,4-Trimethyl benzene

Benzene, ethyl-

Benzene, 1,2-dimethyl-

Phenol

Benzene, 1,4-dimethyl-

Xylenes (o-, m-, p- isomers)

Mass RTK Substances (>1%) :

Barium sulfate

Kaolin

Quartz

Talc

BUTYL ACETATE

Penn RTK Substances (>1%) :

Barium sulfate

Kaolin

Quartz

Talc

BUTYL ACETATE

Penn Special Hazardous Substances (>.01%) :

(No Product Ingredients Listed)

RCRA Status:

(No Product Ingredients Listed)

N.J. RTK Substances (>1%) :

Barium sulfate

Kaolin

Quartz

Talc

BUTYL ACETATE

N.J. Special Hazardous Substances (>.01%) :

BUTYL ALCOHOL

Cumene

Benzene, ethyl-

Isobutyl alcohol

Benzene, 1,2-dimethyl-

Phenol

Quartz

Talc

BUTYL ACETATE

Benzene, 1,4-dimethyl-

Xylenes (o-, m-, p- isomers)

N.J. Env. Hazardous Substances (>.1%) :

1,2,4-Trimethyl benzene

Benzene, ethyl-

Benzene, 1,2-dimethyl-

Phenol

Benzene, 1,4-dimethyl-

Xylenes (o-, m-, p- isomers)

Proposition 65 - Carcinogens (>0%):

Cumene

Benzene, ethyl-

Quartz

Proposition 65 - Female Repro Toxins (>0%):
(No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0%):
(No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0%):
(No Product Ingredients Listed)

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

- H225 Highly flammable liquid and vapor.
- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H341 Suspected of causing genetic defects.
- H361 Suspected of damaging fertility or the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

The following sections have changed since the previous revision.

- SECTION 2: Hazards identification
- SECTION 3: Composition/information on ingredients
- SECTION 9: Physical and chemical properties
- SECTION 11: Toxicological information
- SECTION 12: Ecological information
- SECTION 14: Transport information

End of Document